

Hexagonal V-belt


- For drives where power must be transmitted by both the top and bottom of the belt.
- Belts flex equally well in both directions for positive pulley contact.
- Good for serpentine or reverse bend drives.
- Oil and heat resistant, static conductive.

Product Code

AA - 105

Double Angle A Section

Belt Code, 105 inches



	TW	H
AA	1/2 in - 12.7 mm	13/32 in - 10.2 mm
BB	21/32 in - 16.7 mm	17/32 in - 13.4 mm
CC	7/8 in - 22.2 mm	11/16 in - 17.4 mm

AA			
Belt No.	Outside Length (Inch)	Belt No.	Outside Length (Inch)
AA 51	54.4	AA 92	95.4
AA 55	58.4	AA 96	99.4
AA 60	63.4	AA 105	108.4
AA 62	65.4	AA 107	110.4
AA 64	67.4	AA 112	115.4
AA 66	69.4	AA 120	123.4
AA 68	71.4	AA 128	131.4
AA 70	73.4		
AA 73	76.4		
AA 75	78.4		
AA 78	81.4		
AA 80	83.4		
AA 84	87.4		
AA 85	88.4		
AA 90	93.4		

BB			
Belt No.	Outside Length (Inch)	Belt No.	Outside Length (Inch)
BB 43	47.6	BB 155	159.6
BB 45	49.6	BB 157	161.6
BB 51	55.6	BB 158	162.6
BB 53	57.6	BB 162	166.6
BB 54	58.6	BB 168	172.6
BB 55	59.6	BB 169	173.6
BB 60	64.6	BB 173	177.6
BB 68	72.6	BB 180	184.6
BB 71	75.6	BB 182	186.6
BB 72	76.6	BB 190	194.6
BB 73	77.6	BB 195	199.6
BB 74	78.6	BB 210	214.6
BB 75	79.6	BB 225	228.1
BB 76	80.6	BB 226	229.1
BB 77	81.6	BB 228	231.1
BB 78	82.6	BB 230	233.1
BB 81	85.6	BB 240	243.1
BB 83	87.6	BB 255	258.1
BB 85	89.6	BB 267	270.1
BB 90	94.6	BB 270	273.1
BB 92	96.6	BB 273	276.1
BB 93	97.6	BB 277	280.1
BB 94	98.6	BB 278	281.1
BB 95	99.6	BB 285	288.1
BB 96	100.6	BB 300	303.1
BB 97	101.6	BB 330	333.1
BB 103	107.6		
BB 105	109.6		
BB 107	111.6		
BB 108	112.6		
BB 111	115.6		
BB 112	116.6		
BB 116	120.6		
BB 117	121.6		
BB 118	122.6		
BB 119	123.6		
BB 120	124.6		
BB 123	127.6		
BB 124	128.6		
BB 128	132.6		
BB 129	133.6		
BB 130	134.6		
BB 136	140.6		
BB 140	144.6		
BB 144	148.6		

CC			
Belt No.	Outside Length (Inch)	Belt No.	Outside Length (Inch)
CC 75	81.4	CC 162	168.4
CC 81	87.4	CC 173	179.4
CC 85	91.4	CC 180	186.4
CC 90	96.4	CC 195	201.4
CC 96	102.4	CC 210	216.4
CC 105	111.4	CC 221	227.4
CC 112	118.4	CC 225	229.4
CC 119	125.4	CC 240	244.4
CC 120	126.4	CC 255	259.4
CC 125	131.4	CC 270	274.4
CC 128	134.4	CC 300	304.4
CC 136	142.4	CC 330	334.4
CC 144	150.4	CC 360	364.4
CC 148	154.4	CC 390	394.4
CC 158	164.4	CC 420	424.4